

The Skipper unit

Top cap

This can screw off to allow the attachment of accessories such as the light and sign holder.

Tape end clip

This attaches to the next Skipper unit or accessory.

Tape

Each Skipper unit contains 9m (30ft) of tape.

Locking button

For use in windy conditions. Stops unwanted spooling of tape (tape will still retract).

Tape slot

These are the receptors for tape end clips from other Skipper units.

Screw holes

Use these to screw the Skipper unit into a permanent fixture.



IMPORTANT

Always walk the tape back into the unit to prevent it from folding within the unit

More products from Skipper

Skipper road cone ▶

This revolutionary two-piece cone includes an incorporated helix which deflects wind and adds to stability. It can also facilitate an optional weight ring, and its glass bead sleeve has greater reflectivity than other cones.



Skipper post & base system ▶

The Skipper Post's great versatility allows it to be used on both hard and soft ground, indoors and outdoors. The unique, interchangeable base allows it to be sunk into the ground with a spike or attached to its sturdy base for use on hard surfaces.

Call Aspli Safety Ltd
0113 2461 550

For more information on this product

Using your Skipper units

Avoid damage, improve lifespan and get the most out of the total safety management solution.

INCORRECT USE	CORRECT USE	FEATURES
<p>DO NOT allow the tape end to retract on its own. Walk it back into the unit</p>	<p>1</p> <p>Click the Skipper unit on top of the cone or post</p>	<p>Use the clip to attach to other Skipper units or accessories</p>
<p>DO NOT retract or pull tape with lock on. This will cause premature unit failure</p>	<p>2</p> <p>Pull the tape out to the desired length</p>	<p>Tape can wrap around an object and attach to itself</p>
<p>DO NOT immerse the unit in water</p>	<p>3</p> <p>Click the tape into the next Skipper unit or receiver</p>	<p>Use screw fitting for permanent fixture</p>
<p>DO NOT crease the tape or allow the unit to become contaminated</p>	<p>4</p> <p>Then pull out the tape from the next unit</p>	<p>Each Skipper unit has multi-point connectivity</p>

IMPORTANT NOTICE

Tape may be prone to fading if left in direct sunlight for very long periods.

To maximise unit life it is VERY IMPORTANT to observe the guidelines above. Failure to do so could seriously affect the performance of the Skipper unit and risk invalidating the guarantee.